

ShenZhen ZhengDaSheng Chemical Co., LTD

Contact: Dc Lau

Email:sale01@epoxyresinfactory.com Website:www.zdschemical.com Phone/Whatsapp: +8613760164300

Address:4F, Longyuntong Building, No. 164-5 Pengda Road, Longgang District, Shenzhen

UV Adhesive for Plastic

Model	Application	Appearance	Viscosity /cps	Hardness/Shore	Curing energy mj	Remark
ZDS3206-1	Bonding of acrylic, plastic products, PET and other materials	Transparent liquid	20±5	/	880mj (50W LED light)	
ZDS3206-1 fluorescence	ABS bonded to ABS to increase fluorescence	Transparent or yellowish liquid	20~25fluorescence	50~60D	880mj (50WLED365/395)	
ZDS3206-2	Bonding acrylic to stainless steel, aluminum cake and other metals	Transparent liquid	20±5	/	880mj (50W LED light)	
ZDS3209X6	plastic metal, hook plastic					
ZDS3226	PC sticks to PC, PC/glass, surface	Transparent liquid	1400±10	45A	500mj (50W LED	
ZDS3309X	All kinds of traceless hooks, plastic/glass/metal bonding	yellowish liquid	600±100	48D	800mj (50W LED light)	
ZDS3309X6	Mainly used for traceless hooks, suitable for PET, PC, PMMA, PS and other plastics and plastics, plastics and glass metal bonding	Transparent or yellowish liquid	710±100	48D	800mj (50WLED365/396)	

ZDS3310C	TPU bonding to PC, hook bonding, good resistance to high temperature, low temperature and high humidity, no yellowing	Transparent liquid	380±30	75±5	200mj (50W LED light)	
ZDS3310D2	The bonding between TPU and PC products, and the hook bonding between TPU, have good resistance to high temperature, low temperature and high humidity, no yellowing, high bonding strength and no whitening.	Transparent liquid	380±30	75±5	200mj (50W LED light)	
ZDS3311	Bonding of PC/PVC/PET/PS, etc., plastic to plastic, plastic to metal	Transparent liquid	500±50	55D	800mj (50W LED light)	
ZDS3311-1	Bonding of PC/PVC/PET/PS, etc., plastic to plastic, plastic to metal	Transparent liquid	500±100	55D	800mj (50W LED light)	
ZDS3311X	Plastic/ABS/glass, metal, etc. bonding	Transparent liquid	1000±100	55D	800mj (50W LED light)	
ZDS3311H	PS bonded to PVC, thickened version of ZDS3311	Transparent or yellowish liquid	2100	55A	500mj (50W LED light365/395)	
ZDS3311F	Mainly used for bonding glass to PC, PVC, acrylic and other plastic materials. The product is completely transparent after curing, has good resistance to high temperatures and humidity, has good long-term stability, does not turn white or yellow, and is cost-effective	Transparent or yellowish liquid	400±50	55A	800mj (50WLED365/395)	

ZDS3311 Pink	Silicone product surface filling	Pink liquid	500	55A	500mj (50W LED	
ZDS3311-6 Add flavor	plastic hook glue	Transparent or yellowish liquid	500	55A	500mj (50W LED light365/395)	
ZDS3311-8	Bonding acrylic resin for fiber optic cables	Transparent or yellowish liquid	300~400	70~80A	500mj (50W LED light 365/395)	
ZDS3312D / ZDSZ200221A	The bonding of acrylic keychains and large-area acrylic to PET/PVC has low volatility and irritation, and the strength is the same as 3312. a little slower	Transparent liquid	1000			
ZDS3312W	The bonding between acrylic and PET/PVC has good toughness after curing and medium bonding strength.	Transparent or yellowish liquid	paste	20D	100mj (50W LED light 365/396)	
ZDS3313	Traceless hooks for bonding PC/PVC/acrylic and other plastic substrates, with low irritation and high bonding strength	Transparent liquid	500±50		200mj (50W LED light)	
ZDS3316C	Suitable for bonding PET cylinders and folding boxes; strong bonding force, fast curing speed, resistance to cold and heat shock, and good weather resistance.	Transparent or yellowish liquid	350	65D	200-300mj(50W365nmLED)	
ZDS3328	PVC bonded brushed silver hook	Transparent liquid	110~140	75D	200mj (50W LED	
ZDS3328-B	The bonding of brushed silver hooks has high bonding strength, good stability, and no whitening.	Transparent or yellowish liquid	80-100	75A	500mj (50W LED light)	

ZDS3332	Used for bonding PMMA and PC, with high bonding strength and no cracking after curing; ultra-low viscosity, no bubbles during bonding, completely transparent after curing, good resistance to high temperatures and humidity, good long-term stability, no whitening, no yellowing Change, keychain glue	Transparent or yellowish liquid	1300-1400	35D	880mj (50WLED365/395)	
ZDS3333A / ZDSCB21112603 B	Acrylic and PC bonded PET products have ultra-low viscosity, no bubbles during bonding, completely transparent after curing, good resistance to high temperature and humidity, good long-term stability, no whitening, no yellowing, high bonding strength, and no hardening. cracking. Keychain glue	Transparent or yellowish liquid	600	35D	880mj (50WLED365/395)	

ZDS3333B	Mainly used for bonding PMMA and PC, with high bonding strength and no cracking during curing; the product has ultra-low viscosity, no bubbles during bonding, completely transparent after curing, has good resistance to high temperatures and humidity, has good long-term stability, and does not turn white. , non-yellowing, keychain glue	Transparent or yellowish liquid	800	35D	880mj (50WLED365/395)	
ZDS3333C	Mainly used for bonding PMMA and PC, with high bonding strength and no cracking during curing; the product has ultra-low viscosity, no bubbles during bonding, completely transparent after curing, has good resistance to high temperatures and humidity, has good long-term stability, and does not turn white. , non-yellowing, keychain glue	Transparent or yellowish liquid	1000	35D	880mj (50WLED365/395)	

ZDS3333D / ZDSCB21112603 E	It is used for bonding PMMA and PC. It has high bonding strength and will not crack when cured. It has ultra-low viscosity, no bubbles during bonding, and is completely transparent after curing. It has good resistance to high temperature and humidity and has good long-term stability. It does not turn white or Yellowing, keychain glue	Transparent or yellowish liquid	1400	35D	880mj (50WLED365/395)	
ZDS33355	Acrylic sticks to each other, acrylic sticks to metal	Transparent liquid	2900±200	55±5D	120mj (2KW Medium pressure mercury)	
ZDS33355G	Acrylic sticks to each other, acrylic sticks to metal	Transparent liquid	1600±200	55±5D	120mj (2KW mercury lamp)	
ZDS33355H	Acrylic sticks to each other, acrylic sticks to metal	Transparent liquid	10000~12000	55±5D	120mj (2KW mercury lamp)	
ZDS33355H5	Mainly used in acrylic and acrylic, acrylic and metal, lamp shell wire bonding 3355 high viscosity version	Transparent or yellowish liquid	18000±1000	50±5	880mj (50WLED365/395)	
ZDS33355H-2	Metal to plastic bonding.	Transparent or yellowish liquid	110000-250000	55±5D	120mj (2KW High pressure mercury)	
ZDS33355A2	Acrylic glued to stainless steel (high thixotropy)	paste	12000—20000	55±5D	120mj (2KW mercury lamp)	
ZDS33356 / ZDSJ190618A	acrylic sign	Transparent liquid	330±50	30	800mj (50W LED light)	

ZDS3357	Quicksand mobile phone case, TPU sticky to PC, transparent, not whitening or yellowing, good resistance to high temperature and humidity, resistant to boiling, high and low temperature, good surface drying	good transparency	140±10	75±5	200mj (50W LED light)	
ZDS3358 / ZDSLK190906	Acrylic lampshade, no whitening or yellowing, good resistance to high temperature and humidity	Transparent liquid	2000±200	30±5D	250mj (40W LED light)	
ZDSZB2007141	Dynamic balancing glue (PC/acrylic/PVC, etc.)	Transparent liquid	900±50	25D	1200mj (50WLED light)	
ZDSZB2101191	Mix with PVC solution to increase the speed of curing and molding	Transparent liquid	10		1200mj (50WLED light)	
ZDSCB22091401	Mainly used for bonding PMMA and PC, with high bonding strength and no cracking during curing; the product has ultra-low viscosity, no bubbles during bonding, completely transparent after curing, has good resistance to high temperatures and humidity, has good long-term stability, and does not turn white. , non-yellowing, keychain glue	Transparent or yellowish liquid	1000	40~50D	880mj (50WLED365/395)	

ZDSCB2203023	Mainly used for bonding PMMA and PC, with high bonding strength and no cracking after curing. Ultra-low viscosity, no bubbles in the bonding, completely transparent after curing, good resistance to high temperatures and humidity, good long-term stability, no whitening, no yellowing, affordable. keychain	Transparent or yellowish liquid	1000	35D	880mj (50WLED365/395)	
ZDSCB21092701	Mainly used for bonding PMMA and PC, with high bonding strength and no cracking when cured; ultra-low viscosity, no bubbles in bonding, completely transparent after curing, good resistance to high temperature and humidity, good long-term stability, no whitening, no Yellowing. rowing machine	Transparent or yellowish liquid	215	62D	880mj (50WLED365/395)	Rowing machine
ZDSCB2107053	Mainly used for bonding PMMA and PC, with high bonding strength and no cracking when cured; ultra-low viscosity, no bubbles in bonding, completely transparent after curing, good resistance to high temperature and humidity, good long-term stability, no whitening, no Yellowing. rowing machine	Transparent or yellowish liquid	130	62D	880mj (50WLED365/395)	Rowing machine

ZDSCB22072201	Mainly used for bonding PMMA and PC, with high bonding strength and no cracking when cured; ultra-low viscosity, no bubbles in bonding, completely transparent after curing, good resistance to high temperature and humidity, good long-term stability, no whitening, no Yellowing. Rowing machine, surface dry.	Transparent or yellowish liquid	300	70D	880mj (50WLED365/395)	
ZDSCB2204201	Mainly used for bonding PMMA and PC, with high bonding strength and no cracking when cured; ultra-low viscosity, no bubbles in bonding, completely transparent after curing, good resistance to high temperature and humidity, good long-term stability, no whitening, no Yellowing. rowing machine	Transparent or yellowish liquid	500	62D	880mj (50WLED365/395)	
ZDSCB22030703	Used for traceless hooks, suitable for bonding PET, PC, PMMA, PS and other plastics to plastics; completely transparent after curing, with good resistance to high temperature and humidity, good long-term stability, no whitening, no yellowing	Transparent or yellowish liquid	740	75D	500mj (50W LED light365/395)	

ZDSCB22051901	Used for traceless hooks, suitable for bonding PET, PC, PMMA, PS and other plastics to plastics; completely transparent after curing, with good resistance to high temperature and humidity, good long-term stability, no whitening, no yellowing, better than 3313	Transparent or yellowish liquid	600-700	75D	500mj (50W LED light365/395)	Awaiting production, good adhesion
ZDSCB2206201	Plastic, PET, plastic+glass, plastic+metal	Transparent or yellowish liquid	650	45~50D	880mj (50WLED365/395)	
ZDSWB-22071201	PA bonded nylon	Transparent or yellowish liquid	1000~3000	78A	880mj (50WLED365/395)	
ZDSWB-22071202	PA bonding	Transparent or yellowish liquid	1000~3000	78A	880mj (50WLED365/395)	
ZDSCD22083102	Filter material bonding, test the surface adhesion of the glue	Transparent or yellowish liquid	20	85D	880mj (50WLED365/395)	
ZDSCD22083104	Filter material bonding, test the surface adhesion of the glue	Transparent or yellowish liquid	40	85D	880mj (50WLED365/395)	
ZDSCD22083106	Filter material bonding, test the surface adhesion of the glue	Transparent or yellowish liquid	60	85D	880mj (50WLED365/395)	
ZDSCD22083108	Filter material bonding, test the surface adhesion of the glue	Transparent or yellowish liquid	80	85D	880mj (50WLED365/395)	
ZDSCC2206301B lue	PPT bonding circuit for chassis	blue liquid	35000~55000thixotropy	40D	880mj (50WLED365/395)	
ZDSCA2206301 luminous green	Luminous glue phone case, phone watch screen	light green liquid	12000~30000thixotropy	75D	500mj (50W LED light365/395)	
ZDS3329B	Brushed silver hook					

ZDSCB2204201	Acrylic, PC bonding, high temperature and humidity resistance	Transparent or yellowish liquid	500	62D	880mj (50WLED365/395)	
ZDSWB22070801	plastic bonding					
ZDSCB22030705	Mainly used for traceless hooks, suitable for bonding PET, PC, acrylic, PS and other plastics to plastics	Transparent or yellowish liquid	1160	75D	500mj (50W LED light365/395)	
ZDSCB2206071	Acrylic and PC bonding keychain glue with high bonding strength	Transparent or yellowish liquid	1300-1400	35D	880mj (50WLED365/395)	
ZDSCB22030701	Acrylic, PC and other plastic bonding	Light green slightly turbid or transparent liquid				
ZDSWB22072702	Printing paper bonding					
ZDSCB2207051	plastic bonding					
ZDSCB22091401	Acrylic, PC bonding	Transparent or yellowish	1000-1100	40-50D	880mj	
ZDSCB22091401 A	plastic bonding					
ZDSCB22102101	Glue on plastic	Light yellow liquid	8000-9000	75-80D	400-800mj (365 point light)	
ZDSCB22072201	Mainly used for bonding between PC, acrylic and acrylic, acrylic and metal, lamp housing wires	Transparent or yellowish liquid	300	55±5D	120mj (2KW High pressure mercury lamp)	

ZDSCB22091701	Mainly suitable for PET, PC, acrylic, PS and other plastics and plastics, plastics and glass metal bonding	Transparent or yellowish liquid	8000/20R~20000/5R	55	800mj (50WLED365/395)	
---------------	--	---------------------------------	-------------------	----	--------------------------	--